




funiiscabluri@gmail.com

CABLU METALIC ANTIGIRATORIU SPECIAL 35 X 7 R.2160 N/mm²



EN 12385/4

| Ø Cablu mm | CONSTRUCTIE | Ø FIRE Externe mm | MASA g/m | REZISTENTA | |
|------------------|----------------------------------|-------------------------|-------------|------------|-------|
| | | | | kg | kN |
| 10 | | 0,50 | 450 | 8.520 | 83,58 |
| 11 | | 0,54 | 540 | 10.200 | 100 |
| 12 | | 0,60 | 640 | 12.100 | 119 |
| 13 | | 0,65 | 750 | 14.500 | 142 |
| 14 | | 0,70 | 870 | 16.800 | 165 |
| 15 | | 0,75 | 1.010 | 19.500 | 191 |
| 16 | | 0,78 | 1.135 | 22.100 | 217 |
| 17 | | 0,84 | 1.305 | 24.700 | 242 |
| 18 | | 0,90 | 1.450 | 27.600 | 271 |
| 19 | 7 x 7 + 12 x 7 + 16 x 7 = 35 x 7 | 0,96 | 1.620 | 31.400 | 308 |
| 20 | | 0,99 | 1.770 | 34.300 | 336 |
| 21 | | 1,05 | 1.950 | 38.000 | 373 |
| 22 | | 1,10 | 2.140 | 42.100 | 413 |
| 24 | | 1,20 | 2.575 | 50.300 | 493 |
| 26 | | 1,31 | 3.050 | 58.800 | 576 |
| 28 | | 1,41 | 3.520 | 65.900 | 646 |
| 30 | | 1,50 | 4.000 | 74.800 | 733 |
| 32 | | 1,60 | 4.580 | 84.600 | 829 |
| 34 | | 1,70 | 5.170 | 95.600 | 937 |