




funiiscabluri@gmail.com

## CABLU METALIC ZINCAT 6X19+NFC DX(114FIRE)

EN 12385/4 R.1770 N/mm<sup>2</sup>

R 200 kg/mm<sup>2</sup>



| Ø<br>FUNDE | SEZIONE<br>METALLICA | Ø FILI<br>ESTERNI | PESO | CARICO ROTTURA           |        |
|------------|----------------------|-------------------|------|--------------------------|--------|
|            |                      |                   |      | R 180 kg/mm <sup>2</sup> |        |
| mm         | mm <sup>2</sup>      | mm                | g/m  | kg                       | kN     |
| 3          | 3,58                 | 0,20              | 33   | 545                      | 5,34   |
| 4          | 6,05                 | 0,26              | 55   | 925                      | 9,07   |
| 5          | 9,16                 | 0,32              | 84   | 1.400                    | 13,73  |
| 6          | 14,3                 | 0,40              | 130  | 2.150                    | 21,09  |
| 7          | 18,9                 | 0,45              | 170  | 2.850                    | 27,95  |
| 8          | 22,4                 | 0,50              | 200  | 3.350                    | 32,86  |
| 9          | 32,2                 | 0,60              | 290  | 4.850                    | 47,57  |
| 10         | 37,8                 | 0,65              | 340  | 5.700                    | 55,90  |
| 11         | 43,9                 | 0,70              | 400  | 6.600                    | 64,74  |
| 12         | 57,3                 | 0,80              | 520  | 8.000                    | 78,40  |
| 13         | 64,7                 | 0,85              | 590  | 9.700                    | 95,15  |
| 14         | 72,5                 | 0,90              | 660  | 10.800                   | 105,94 |
| 16         | 98,7                 | 1,05              | 900  | 14.800                   | 145,18 |
| 18         | 129                  | 1,20              | 1100 | 19.300                   | 189,33 |