




funiiscabluri@gmail.com

CABLU METALIC 6X36IWRC DX WARRINGTON SEALE (216+49)

zincat,mat.gresat



EN 12385/4 R.1770,1960,2150 N/mm²

Ø CABLU mm	Ø FIRE EXTERNE mm	MASA g/m	REZISTENTA			
			180 kg/mm ² kg	1770 N/mm ² kN	220 kg/mm ² kg	2150 N/mm ² kN
8	0,44	255	4.200	41,2		
10	0,55	400	6.500	63,7	8.870	87
11	0,61	500	7.700	76,2	10.500	103
12	0,67	600	9.700	95,1	12.350	121
13	0,72	710	10.900	107	14.000	137
14	0,78	815	13.100	128	16.600	163
15	0,83	950	14.500	142	19.000	186
16	0,89	1.070	16.800	165	21.300	209
18	1	1.350	22.500	221	27.000	265
19	1,06	1.520	23.200	228	32.000	314
20	1,11	1.680	27.000	265	34.000	333
22	1,22	2.030	32.600	320	41.000	402
24	1,33	2.400	38.400	377	46.800	459
26	1,44	2.830	45.000	441	56.000	549
28	1,55	3.280	50.500	495	65.000	637
30	1,66	3.750	60.000	588	75.000	735
32	1,78	4.250	66.800	655	82.000	804
34	1,89	4.800	75.100	736	***	
36	2	5.400	84.000	824	***	
38	2,11	5.860	92.600	908	***	
40	2,22	6.600	105.000	1.030	***	