




funiiscabluri@gmail.com

## CABLURI METALICE CU INALTA REZISTENTA 8 TORONI



EN 12385/4 R.1960 N/ mm<sup>2</sup>

Ø CABLU mm	CONSTRUCTIE	Ø FIRE EXTERNE mm	MASA g/m	REZISTENTA R.1960 N/mm <sup>2</sup>	
				kg	kN
6	99 fire	0,52	161	3.100	30,41
7		0,60	211	4.100	40,22
8		0,69	272	5.300	52
9		0,78	248	6.750	66,22
10		0,87	433	8.400	82,33
11	235 fire	0,72	541	10.500	103
12		0,78	636	12.300	121
13		0,84	744	14.400	141
14		0,90	893	17.300	170
15		0,99	1.030	19.900	195
16		1,05	1.150	22.200	218
17		1,11	1.310	25.300	248
18		1,17	1.450	28.000	275
19		1,23	1.610	31.100	305
20		1,32	1.790	34.700	340
22	283 fire	1,14	2.230	43.200	424
24		1,26	2.660	51.400	504
26		1,35	3.100	60.000	588
28	311 fire	1,47	3.600	69.800	684
30		1,58	4.130	80.000	784
32	423 fire	1,56	4.760	92.200	904
34		1,64	5.380	104.000	1.020

\*LA CERERE OFERIM CABLURI SPECIALE DE ORICE FEL DE CONSTRUCTIE, PLASTIFICATE, DE ORICE MARCA  
CERTIFICATE LA NORMELE IN VIGOARE